



Bearing NO.	Shape Dimension(mm)						r		Basic Load Rating(N)		Weight (kg)
	d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	min(mm)	min(inch)	Dynamic(Cr)	Static(Cor)	
S6300	10	0.3937	35	1.3780	11	0.4331	0.6	0.0236	7640	3470	0.0530
S6301	12	0.4724	37	1.4567	12	0.4724	1	0.0394	9700	4190	0.0600
S6302	15	0.5906	42	1.6535	13	0.5118	1	0.0394	11400	5430	0.0820
S6303	17	0.6693	47	1.8504	14	0.5512	1	0.0394	13580	6580	0.1150
S6304	20	0.7874	52	2.0472	15	0.5906	1.1	0.0433	15940	7880	0.1490
S6305	25	0.9843	62	2.4409	17	0.6693	1.1	0.0433	22380	11490	0.2320
S6306	30	1.1811	72	2.8346	19	0.7480	1.1	0.0433	27000	15200	0.3490
S6307	35	1.3780	80	3.1496	21	0.8268	1.5	0.0591	33500	19200	0.4640
S6308	40	1.5748	90	3.5433	23	0.9055	1.5	0.0591	40500	24000	0.6360