



Bearing Number	Dimensions			Basic Load Rating		Limiting Speed (X1000 RPM)		Weight(Kg)
	d	D	B	Cr(N)	Cor(N)	Grease	Oil	
R8	12.7 mm	28.575 mm	6.35 mm	1149	511	27	32	11.6
R8 2rs	12.7 mm	28.575 mm	7.938 mm	1149	511	27	32	24.1
R8zz	12.7 mm	28.575 mm	7.938 mm	1149	511	27	32	24.1
R10	15.875 mm	34.925 mm	7.142 mm	1585	735	21	25	23.5
R10 2rs	15.875 mm	34.925 mm	8.733 mm	1585	735	21	25	38.1
R10zz	15.875 mm	34.925 mm	8.733 mm	1585	735	21	25	38.1
R12	19.05 mm	41.275 mm	7.938 mm	2477	1177	17	21	53.1
R12 2rs	19.05 mm	41.275 mm	11.113 mm	2477	1177	17	21	69.3
R12zz	19.05 mm	41.275 mm	11.113 mm	2477	1177	17	21	69.3
R14	22.225 mm	47.625 mm	9.525 mm	2658	1307	10	12	78
R14 2rs	22.225 mm	47.625 mm	12.7 mm	2658	1307	10	12	78
R14zz	22.225 mm	47.625 mm	12.7 mm	2658	1307	10	12	78
R16	25.4 mm	50.8 mm	9.525 mm	2652	1307	9	11	87
R16 2rs	25.4 mm	50.8 mm	12.7 mm	2652	1307	9	11	87



## Inch Deep Groove Ball bearings R Series

R16zz	25.4 mm	50.8 mm	12.7 mm	2652	1307	9	11	87
R18	28.575 mm	53.975 mm	9.525 mm	3492	1817	8	10	91
R18 2rs	28.575 mm	53.975 mm	12.7 mm	3492	1817	8	10	91
R18zz	28.575 mm	53.975 mm	12.7 mm	3492	1817	8	10	91
R20	31.75 mm	57.15 mm	9.525 mm	3695	1986	7	9	102
R20 2rs	31.75 mm	57.15 mm	12.7 mm	3695	1986	7	9	102
R20zz	31.75 mm	57.15 mm	12.7 mm	3695	1986	7	9	102
R22	34.925 mm	63.5 mm	11.113 mm	4067	2247	7	8	105
R22 2rs	34.925 mm	63.5 mm	14.288 mm	4067	2247	7	8	105
R22zz	34.925 mm	63.5 mm	14.288 mm	4067	2247	7	8	105
R24	38.1 mm	66.675 mm	11.113 mm	4426	2446	5	6	140
R24 2rs	38.1 mm	66.675 mm	14.288 mm	4426	2446	5	6	140
R24zz	38.1 mm	66.675 mm	14.288 mm	4426	2446	5	6	140