



| Bearing Number | Dimensions | | | Basic Load Rating | |
|----------------|------------|-----------|----------|-------------------|--------|
| | d | D | B | Cr(N) | Cor(N) |
| R1038 | 9.525 mm | 15.875 mm | 3.967 mm | 96 | 53 |
| R1038 2RS | 9.525 mm | 15.875 mm | 3.967mm | 96 | 53 |
| R1038zz | 9.525 mm | 15.875 mm | 3.967mm | 96 | 53 |
| R1212 | 12.7 mm | 19.05 mm | 3.967 mm | 111 | 71 |
| R1212 2RS | 12.7 mm | 19.05 mm | 3.967 mm | 111 | 71 |
| R1212zz | 12.7 mm | 19.05 mm | 3.967 mm | 111 | 71 |
| R1458 | 15.875 mm | 22.225 mm | 3.967 mm | 116 | 81 |
| R1458 2RS | 15.875 mm | 22.225 mm | 3.967mm | 116 | 81 |
| R1458zz | 15.875 mm | 22.225 mm | 3.967 mm | 116 | 81 |
| R1634 | 19.05 mm | 25.4 mm | 3.967 mm | 127 | 99 |
| R1634 2RS | 19.05 mm | 25.4 mm | 3.967 mm | 127 | 99 |
| R1634zz | 19.05 mm | 25.4 mm | 3.967 mm | 127 | 99 |
| R1878 | 22.225 mm | 28.575 mm | 3.697 mm | 137 | 109 |
| R1878 2RS | 22.225 mm | 28.575 mm | 3.967 mm | 137 | 109 |
| R1878zz | 22.225 mm | 28.575 mm | 3.967 mm | 137 | 109 |
| R2127 | 26.988 mm | 33.338 mm | 3.967 mm | 145 | 128 |
| R2127 2RS | 26.988 mm | 33.338 mm | 3.967 mm | 145 | 128 |
| R2127zz | 26.988 mm | 33.338 mm | 3.967 mm | 145 | 128 |
| R2420 | 31.75 mm | 38.1 mm | 3.967 mm | 154 | 146 |
| R2420 2RS | 31.75 mm | 38.1 mm | 3.967mm | 154 | 146 |
| R2420zz | 31.75 mm | 38.1 mm | 3.967 mm | 154 | 146 |



Inch Thin Wall Bearings

| | | | | | |
|-----------|-----------|-----------|----------|-----|-----|
| R2622 | 34.925 mm | 41.625 mm | 3.967 mm | 163 | 165 |
| R2622 2RS | 34.925 mm | 41.625 mm | 3.967 mm | 163 | 165 |
| R2622zz | 34.925 mm | 41.625 mm | 3.967 mm | 163 | 165 |
| R2824 | 38.1 mm | 44.45 mm | 3.967 mm | 166 | 174 |
| R2824 2RS | 38.1 mm | 44.45 mm | 3.967 mm | 166 | 174 |
| R2824zz | 38.1 mm | 44.45 mm | 3.967 mm | 166 | 174 |
| R3026 | 41.625 mm | 47.625 mm | 3.967 mm | 175 | 192 |
| R3026 2RS | 41.625 mm | 47.625 mm | 3.967 mm | 175 | 192 |
| R3026zz | 41.625 mm | 47.625 mm | 3.967mm | 175 | 192 |